

Grille Installation Instruction

Rev. 180701

Part#	GR07DFE16S	Application	For 2007-2010 GMC Sierra 2500 HD/3500 HD With
			For 2007-2010 GMC Sierra 2500 HD/3500 HD With Logo Show

		Item	Part Name	QTY	Description	Item	Part Name	QTY	Description		
Parts L	c+	1 Mesh Grille 1 Stainless		Stainless steel	4	Bolts	6	8 -32×2.5"			
Parts Li	Si	2	Flange Brackets	6		5	K-Lock Nuts	6	8-32		
		3	Wrench 1								
Install Notes: Overlay Replacement											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and re-attach after installation.										
3	Center the grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille. Be sure the bolts are through the OEM grille shell.										
4	Place one bolt through each of the holes on the grille. From the rear, place a flange bracket on each screw. Now thread a nut on each bolt. Then use the wrench to thread a bolt on the grille.										
5	Make sure the grille is centered and tighten the fasteners. But do not over-tighten.										
6	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!