

PATENT PRODUCT Grille Installation Instruction

Rev. 20201201

| Part# | G65271C&J&S | | C&J&S | Application | | For 1994-1998 GMC C/K Pickup Single Lights Only With Logo Show | | | | | |
|--|--|--|---------------|-------------|-----|--|------|-----------|-----|-------------|--|
| | | Item | Pa | rt Name | QTY | Description | Item | Part Name | QTY | Description | |
| Parts Li | ist | #1 | Billet Grille | | 1 | Stainless Steel | #3 | Lock Nuts | 6 | 6-32 | |
| | | #2 Bolts | | | 6 | 6-32×2" | #4 | Flat Tabs | 6 | | |
| Install Notes: Overlay $\boxed{\hspace{1em}}$ Replacement $\boxed{\hspace{1em}}$ Drill $\boxed{\hspace{1em}}$ Cut $\boxed{\hspace{1em}}$ | | | | | | | | | | | |
| Step | Description illustration | | | | | | | n | | | |
| 1 | Identify the grille & hardware with parts list. | | | | | | | | | | |
| 2 | Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual. | | | | | | | | | | |
| 3 | Thread a Bolt in each nut welded to the grille. From the rear, place a Flat Tab on each screw. Now thread a Lock Nut on each Bolt. | | | | | | | | | | |
| (6) Bolts (6) Lock Nuts (6) Flat Tabs 4 Make sure the insert is centered and tighten the hardware. | | | | | | | | | | | |
| 4 | | | | | | | | | | | |
| 5 | Rei | Reinstall the plastic shroud with the fasteners removed in Step 2. | | | | | | | | | |
| 6 | Installation completed. | | | | | | | | | | |

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!