




Grille Installation Instruction

Rev. 190901

Part#	GR07FEG82 A/H	Application	For 2007-2014 GMC Yukon Tow Hook Show Not For Hybrid Model/2007-2014 GMC Yukon XL Tow Hook Show Not For Hybrid Model
--------------	------------------	--------------------	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Flat Nuts	4	8#
2	Self Drill Screws	2	8#	4	Truss Head Tapping Screws	4	8×1 1/4"	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Remove the factory license plate from the vehicle. Test fit the billet into the opening. Mark the mounting holes to the plastic in the bumper opening. Drill a 1/8" pilot hole at each mark.	
4	Re-center the grille in place. Secure the billet using the #8 screws provided. The license plate may be re-installed onto the bumper cover. Use the #8 self drill screws to secure the license plate.	
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
We are not responsible for any damage caused by the installation. Thank you for choosing our product!