



PATENT PRODUCT Grille Installation Instruction

Rev. 20200801

Part#	G65782C&J&S	Application	For 2007-2014 GMC Yukon Tow Hook Show Not For Hybrid Model / 2007-2014 GMC Yukon XL Tow Hook Show Not For Hybrid Model
--------------	-------------	--------------------	--

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
Parts List	#1	Billet Grille	1	Stainless Steel	#3	Flat Nuts	4	8#
	#2	Self Drill Screws	2	8#	#4	Truss Head Tapping Screws	4	8×1 1/4"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.	
3	Remove the factory license plate from the vehicle. Test fit the billet into the opening. Mark the mounting holes to the plastic in the bumper opening. Drill a 1/8" pilot hole at each mark.	
4	Re-center the grille in place. Secure the billet using the Truss Head Tapping Screws and Flat Nuts provided. The license plate may be re-installed onto the bumper cover. Use the #8 Self Drill Screws to secure the license plate.	
5	Make sure the insert is centered and tighten the hardware.	
6	Reinstall the plastic shroud with the fasteners removed in Step 2.	
7	Installation completed.	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!