

Installation completed.

PATENT PRODUCT Grille Installation Instruction

Rev. 20210301

AUTO PARTS SPECIALIST INC.												
Part#	G6	666515C&J&S		Application		For 20	For 2007-2012 GMC Acadia					
		Item	Part Name		QTY	Description		Item	Part Name	QTY	Description	
Parts Li	st	#1	Billet Grille		1	Stainless Steel		#3	Truss Head Tapping Screws	4	8x1"	
		#2 Flat Nuts		4	8#							
Install Notes: Overlay												
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.											
	Do so by removing the plastic push pull style rivets as shown, (Fig 1) . Using a small regular screwdriver lift on the center portion of the rivet to release. Remove the core support cover.											
4	With core support cover removed, remove the (6) phillips head screws holding top portion of the stock grille shell in place, (Fig 2). Also remove (2) more of the plastic push pull style rivets located just outside of the chrome on stock shell on driver and passenger side of shell, (Fig 3). This allow you to reach behind the stock grille shell.											
5	Place billet grille into opening and center. Attach billet grille by using the supplied screws and nuts. (Fig 4)											
Fig 1												
6	Make sure the insert is centered and tighten the hardware.											
7	Reinstall the plastic shroud with the fasteners removed in Step 2.											

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!