

## PATENT PRODUCT Grille Installation Instruction

Rev. 200801

Part#	GR07FGH60J	Application	2007-2013 GMC Sierra 1500 New Body Style
-------	------------	-------------	--

Don't Nome OTV Decembring Home

		Item	Part Name	QTY	Description	Item	Part Name	QTY	Description	
		1	Billet Grille	2	Stainless steel	4	Truss Head Tapping Screws	4	8# × 3 ″	
Parts L	ist	2	Two-hole Tabs	2	8#	5	U- Clip Nuts	8		
		3	Screws	4	8# <b>x</b> 3"	6	Powder Coated Brackets	2		
						7	Powder Coated Double Punch Bracket	1		
Install Notes: Overlay × Replacement √ Drill √ Cut ×										
Step	Description					illustration				
1	Identify the grille & hardware with parts list.									
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.									
3	Start with the upper section. Place one screw through each of the welded tabs on the billet grille.									
4	Place a U-clip nut over each of the holes on the two-hole flat tabs.									
5	Place a tab behind the grille shell in line with were the screw comes through. Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center.									
6	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.									
7	Move on to the lower section. Remove the entire license plate bracket.If equipped remove the factory tow hooks.									
8	Remove the billet grille from the box and protective wrapping. Center the billet grille into the bumper opening and mark and drill the mounting holes									
9	Install the fully threaded studs into the threaded tabs on the backside of the billet grille.Re-center the billet grille into the opening with the studs going through the mounting holes drilled									

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!



## PATENT PRODUCT Grille Installation Instruction

Rev. 200801

Part#	GR07FGH60J	Application	2007-2013 GMC Sierra 1500 New Body Style			
10	Place the single hole powder coated brackets over the 2 outer studs and hold in place using the k-lock nuts.					
11	Place the powder coated double punch brackets over the fully threaded studs in the center of the billet grille and hold in place using the k-lock nuts.					
12	Make sure the billet grille is centered and tighten the fasteners.					
13	Reinstall the black plastic cover which was removed in step 2.					
14	Installation completed!!!					

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!