

## PATENT PRODUCT Grille Installation Instruction

Rev. 20220801

Part#	G75622K&S Application		on	For 2019-UP GMC Sierra 1500							
		ltem	Pa	rt Name	QTY	Descrip	tion	ltem	Part Name	QTY	Description
Parts Li	ist	#1 Mesh		rille	1	Stainless Steel		#3	Flat Nuts	11	#8
		#2	Screws		11	11 #8x ¾"					
Install Notes: Overlay $\times$ Replacement $\checkmark$ Drill $\checkmark$ Cut $\checkmark$											
Step	p Description illustration							on			
1	Identify the grille & hardware with parts list.										
2	Remove the plastic core support cover shroud. There will be a number of Plastic "Push Rivets" that secure the cover. Remove and set aside for re- installation. Remove Cover and set aside, (Figs 1&2).										
3	Remove the factory hardware that Secures the grille assembly to the top of the core support, (Fig 3). It is the time to loosen the vehicle wheel well fender trim. Start at the top middle, and working your way towards the very front of the fender trim where it meets the front bumper, use a tort bit to remove the screws. With the front half fender trim loose and pulled out of the way, (Fig 5). You can access the additional hardware that secures the plastic lower bumper valance. Remove these bolts and set aside all hardware for re-installation.(Figs 4-5).										
bille did det did did did did did terre in terre interaction. (Fig. 9 + 0): FIG.3 $FIG.4$ $FIG.5$ $FIG.5$ $FIG.5$											
4 Remove the vehicles fascia located directly above the front bumper, below the grille. Pull out the fascia away from where it meets the front fender. You will need to unfasten several tabs that underneath headlights, (Figs 6-8).											
$\begin{tabular}{ c c c c } \hline \hline \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ $											



PATENT PRODUCT Grille Installation Instruction

Rev. 20220801


Part#	G75622K&S	Application	For 2019-UP GMC Sierra 1500						
5	With the fascia removed you can now access several bolts at the bottom below the grille lip and above the vehicle bumper and also located (2) more at the lower corners. Remove all hardware that attaches the grille assembly to vehicle, (Figs 9-10).								
FIG 9			FIG 10						
6	Using both hands, remove the bottom corners of each side of the grille. This will release the grille from the vehicle and allow you to remove it from the core support, (Fig 11).								
7	Flip the grille assembly over and place on a flat cushioned surface or foam pad.								
8	From the grille backside, locate and mark the cutting path using a paint pen as shown in <b>Fig 12</b> .								
9	Place the grille on a protected work surface and begin the cutting process to remove the factory grille black plastic pattern.								
10	From the grilles backside, using a cutoff wheel or similar, carefully cut along the marked line, (Fig 13). Make sure not to cut into the chrome trim on the opposite side of the tool path.								
11	Remove the factory	/ insert form the grill	e as shown in Fig 14.						

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!



PATENT PRODUCT Grille Installation Instruction

Rev. 20220801



The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!