

Grille Installation Instruction

Rev. 130930

Part#		G76516T		A	Application		For 2007-2010 GMC Sierra 2500 / 3500 HD With Logo Show`								
		Item	Part N		ne	QTY	Des		ription	Item	Part Name		QTY	Description	
Parts L	ict	1	Mesh Grille			1	Stainless steel		steel	4	K-Lock Nuts		7	6-32	
Parts L	ısı	2	Stud			7 6-32×2		×21	/2"	5	Flat tab with one hole		1		
		3 Flange Bra			ets	6									
Install N	lotes: Overlay					placeme	ent	×	Drill	×	Cut	×			
Step	Description							illustration							
1	Identify the grille & hardware with parts list.														
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.														
3	Secure the stud to the threaded holes on the rear of the grille.														
4	Center the grille into the opening of the factory grille shell.Be sure the studs are through the OEM grille shell.														
5	Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell.														
6	Mal	Make sure the grille is centered and tighten the fasteners.													
7	Rei	nstall th	ie black p	olastic	cover v	vhich was	remo	ved i	n step 2.						
8	Inst	allation	complete	ed!!!											

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!