	Grille Installation Instruction											Rev. 150116		
Part#	GR07HEJ12NApplication1994-1999 GMC C/K Pickup With Stacked Lights/Suburban Composite Plastic Lig Main Upper										ced			
Parts L	ist	ltem	Part	Name	QTY	Descrip	tion	Item	F	Part Name	QTY	Description		
		1	Billet Gril	le	1	Aluminum		2	Philli	ip Screws	7	#8×3/4″		
Install Notes: Overlay × Replacement √								Drill 🗸		Cut √				
Step		Description						illustration						
1	Identify the grille & hardware with parts list.													
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Remove bottom indicator lights with star bit.						N/A							
3	Remove bottom indicator lights with star bit.						N/A							
4	Unplug bulbs from side indicate lights.(Remove lenses if painting grille.)						N/A							
5	Remove 7mm bolts,Remove grille from truck						N/A							
6	Tape off face of grille. Then using your jigsaw, carefully cut along the outer portion of the chrome ring. Be careful not to cut the outer portion of the grille shell.Clean up all areas, top and bottom, with flat file until smooth and flat.						N/A							
7	Fit billet piece into factory grille. Carefully line up billet piece in grille. Mark and drill 1/8 <sup>"</sup> holes where vertical bars touch top and bottom of plastic grille. Secure billet piece with blind rivets.						N/A							
8	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.													
9	Re-install grille.							N/A						
10	Installation completed!!!													

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!