

PATENT PRODUCTGrille Installation Instruction

Rev. 20210101

Auto parts specialist inc.															
Part#	G8	35067	C&J&S	Арр	lication	For 1998-2000 GMC Yukon Denali									
		Item	Part Name		QTY	Description		Item	Item Part Name				QTY	Description	
		#1	Billet Gr	Billet Grille		Stainless Steel		#6	Truss Socket Tapping Screws			g Screv	vs 4	10×3/4"	
Parts Li	ist	#2	Big L Ta		2			#7	Truss Head Tapping Screws			Screws		8×3/4"	
	-	#3 #4	Small L Two Ho					#8 #9	U-Clip Nuts Hex Bolts				8 2	8# 1/4"-20×3/4"	
	-	# 4 #5	Flat Bra		2			#10	Kep Nuts				2	1/4 -20 ^ 3/4	
Install N	lote			×	l	cement	√	Dril							
Step				Descrip	tion			illustration							
1	Identify the grille & hardware with parts list.														
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle.														
3	Cut and remove stock grille work a 1/4" reveal behind chrome ring and sad smooth.														
4	Cut and remove stock grille work a 1/4" reveal behind chrome ring and sad smooth Install as shown. Note: You will need to drill a hole where screw goes through grille.														
	billet grille waferhead screw waferhead screw waferhead screws billet grille in 2 places, attaches to side of shell) waterhead screws in 2 places) waterhead screws in 2 places)														
5	Mak	ke sure	the inse	ert is cer	tered and	d tighten the	e hardv	ware. Rei	nstall the	e plastic	shrou	ıd with	the fasten	ers removed in Step 2.	
6	Inst	allatior	n comple	ted.											

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!