

Grille Installation Instruction

Part#	GR07LEG03H			A	Application		1999-2	-2000 GMC Sierra 1500 With Logo Show Main Upper						
		Item	Part Nam		e QTY		Description			ltem	Part Name	QTY	Description	
Parts L	ist	1	Mesh Gr	ille	2	Stain	less stee	el		4	Lock Nut	10	10-24	
		2	Stud		10 10-24× 2 1/2"			1		5	Flat Tab A	4	1	
		3	washer		10 /					6	Flat Tab B	2	1	
Install N	Notes: Overlay			\checkmark	Replace		ent 🗔	< Dril		×	Cut	×		
Step	Description							illustration						
1	Identify the grille & hardware with parts list.						N/A							
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.													
3	Secure the stud to the threaded holes on the rear of the grille.											Studs		
4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell.													
5	Secure grille using the flat tabs and lock nuts and washers from the back side of the OEM grille shell.								4-Flat Tabs A and 8-Lock Nuts and 8-Washers 2-Flat Tabs B and 2-Lock Nuts and 2-Washers					
6	Make sure the grille is centered and tighten the fasteners.													
7	Rei	Reinstall the black plastic cover which was removed in step 2.												
8	Installation completed!!!													

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!