

## Grille Installation Instruction

Rev. 181001

Part# GR08FFE02A/H Application For 2007-2008 Honda Element SC Not For EX/LX

	_	ltem	Part Name	QTY	Description		Item	Part Name	QTY	Description
Parts List		1	Billet Grille	1	Aluminum		3	Flange Nuts	4	M4
2.00		2	Truss Head Screws	4	M4X30		4	Flat Washers	4	
Install	Notes: Overlay			cement ×		Drill	×	Cut ×		
Step	Description					illustration				
1	Ident	tify the	grille & hardware with parts							
2	Optional (for vehicles with black plastic cover under hood). Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.									
3	Place one screw through each of the welded tabs on the billet grille.									
4	Where the screws come through the grille shell, place a nut and washer in align with the screw and tighten. Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center.									
5	Make sure the billet grille is centered and tighten the fasteners, but do not over tighten.									
6	Reinstall the black plastic cover which was removed in step 2.									
7	Installation completed!!!									

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!