

Grille Installation Instruction

Rev. 190301

Part#	(GR08FFE57A/H		Application			For 2008-2010 Honda Accord Coupe Slight Modification Requried For Aero Kit Package					
		Item	Part Name		QTY	Description		Item	Part Name	QTY	Description	
Parts Li	ist	1	Billet Grille		1	Aluminum		3	Screws	4	8#x1"	
		2 Flat Nuts		4	4 8#		4	"J" Hooks	4			
Install Notes: Overlay \checkmark Replacement \times Drill \times Cut \times												
Step	Description						illustration					
1	Identify the grille & hardware with parts list.											
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.											
3	Center the billet grille into the opening of the factory grille shell. Place one screw through each of the welded tabs on the billet grille.											
4	Where the screws come through the grille shell, place a "J" hook and a flat nut in align with the screw and tighten. Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center.											
5	Make sure the billet grille is centered and tighten the fasteners.											
6	Reinstall the black plastic cover which was removed in step 2.											
7	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!