




Grille Installation Instruction

Rev. 180301

| | | | |
|-------|--------------|-------------|-------------------------------------|
| Part# | GR08FFE59A/H | Application | For 2007-2008 Honda Element EX / LX |
|-------|--------------|-------------|-------------------------------------|

| Parts List | Item | Part Name | QTY | Description | Item | Part Name | QTY | Description |
|------------|-----------|---------------|-----|-------------|-----------|---------------------------|-----|-------------|
| | 1 | Billet Grille | 1 | Aluminum | 3 | Cross Head Tapping Screws | 4 | 8x1" |
| 2 | "J" Hooks | 4 | | 4 | Flat Nuts | 4 | 8# | |

Install Notes: Overlay Replacement Drill Cut

| Step | Description | illustration |
|------|---|--|
| 1 | Identify the grille & hardware with parts list. |  |
| 2 | Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation. | |
| 3 | Place one screw through each of the welded tabs on the billet grille. | |
| 4 | Where the screws come through the grille shell, place a "J" hook and a flat nut in align with the screw and tighten. Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center. DO NOT OVER TIGHTEN SCREWS. | |
| 5 | Reinstall the plastic shroud with the fasteners removed in Step 2. | |
| 6 | Installation completed!!! | |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!