

PATENT PRODUCT Grille Installation Instruction

Rev. 150116

Part#		GR08FFE91J		Application		For 2007-2009 Honda CR-V				
		Item	Part Name	QTY	Desc	ription	Item	Part Name	QTY	Description
Parts L	ist	1	Billet Grille	lle 1 Stainles		s steel	3	Flat Nuts	4	8#
		2	Flat Tabs	Tabs 4				Truss Head Tapping Screws	4	8×2″
Install Notes: Overlay V Replacement ×							Drill $\sqrt{}$ Cut \times			
Step	Description						illustration			
1	Identify the grille & hardware with parts list.									
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.									
3	Drill a hole in the top left corner of the billet grille.									
4	Place one screw through each of the welded tabs on the billet grille.									
5	Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille.Be sure the bolts are through the OEM grille shell.									
6	Where the screws come through the grille shell, place a flat nut in align with the screw and tighten. Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center.									
7	Make sure the billet grille is centered and tighten the fasteners.									
8	Reinstall the black plastic cover which was removed in step 2.									
9	Installation completed!!!									

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!