

Grille Installation Instruction

Rev. 190601

Part#		GR08FFF97 A/H			Application		For 2009-2011 Honda Ridgeline With Logo Show				
Parts List		Item	m Part Name		QTY	Description		Item	Part Name	QTY	Description
		1	Billet Grille		1	Aluminum		3	Truss Head Tapping Screws	4	8×3"
		2	Flat Tabs		4		4	U- Clip Nuts	4	8#	
Install N	lote	es: Ov	erlay V		Replac	emen	nt ×	Drill	× Cut ×		
Step	Description							illustration			
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Place one screw through each of the welded tabs on the billet grille.										
4	Place a U-clip nut over the hole on the flat tab.										
5	Where the screws come through the grille shell, place a tab in align with the screw and tighten.										
6	Tighten each of the screws evenly so as not to put the grille in a bind and not to make it go off center.										
7	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!