

Grille Installation Instruction

Part#	GR08FFG66 A/H		Application		For 2009-2011 Honda Civic Coupe						
	Item	Part N	ame	QTY	Description		ltem	Part Name		QTY	Description
Parts Lis	st 1	Billet G	Grille	1	Aluminum		3	Truss Head Screws		4	6-32x2″
	2	Flange	Nuts	4	6-32		4	2-Hole Tabs		2	
Install Notes: Overlay \checkmark Replacement \times						×	Drill	×	Cut ×		
Step	Description						illustration				
1	Identify the	ardware	e with part	s list.	1						
	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.										
3	Place screws through the welded aluminum tabs on the grille.										
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell.										
5	Secure the grille using tabs and flange nuts from backside of the OEM grille shell .										
6	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.										
7	Reinstall the black plastic cover which was removed in step 2.										
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!