

Grille Installation Instruction

Part# GR08FFI55A/H Application For 2012-2015 Honda Pilot

Parts List		Item Part Name		QTY Description		ltem	Part Name	QTY	Description	
		1	Billet Grille	1 Aluminun			3	Toggle Nut	2	6-32
		2	Bolt	2	6-32×1″					
Install Notes: Overlay 🔨 Replacement 🗦					nent ×	Dri	ill ×	Cut	×	
Step	Description					illustration				
1	Identify the grille & hardware with parts list.									
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.									
3	Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille.Be sure the bolts are through the OEM grille shell.									
4		Secure billet grille using the toggle nuts from the back side of the OEM grille shell.					THE	2T	oggle Nuts	
									E.	
5	Make sure the billet grille is centered and tighten the fasteners.									
6	Reinstall the black plastic cover which was removed in step 2.									
7	Inst	allation	completed!!!			And				

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!