



PATENT PRODUCT



Grille Installation Instruction

Rev. 190601

Part#	GR08FGA04 C/S/J	<i>Application</i>	For 2003-2005 Honda Accord Sedan
--------------	----------------------------	--------------------	---

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Stainless steel	4	Truss Head Screws	2	6-32×2"
	2	Washers	2		5	Nylon Lock Nuts	2	6#
	3	'J' Hooks	2					

Install Notes: Overlay Replacement Drill Cut

Step	Description	Illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Place a machine screw in each mount on the billet insert. Install a "J" hook from the back with a Nylon lock nut and washer. Place the billet insert in the bumper opening.	
4	Tighten the nuts down with the "J" hooks catching the rear edge of the bumper cover. Do not over tighten.	
5	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
 Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
 We are not responsible for any damage caused by the installation. Thank you for choosing our product!!