

Grille Installation Instruction

Part#	Н	H67111A/H Application For			For 2001-2	2001-2002 Honda Accord Coupe						
		ltem	Pa	art Name Q		Description		ltem	Part Name	QTY	Description	
Parts List		1	Billet Grille		1	Aluminum		3	Screws	2	8# × 3/4″	
		2	U-Clip Nuts		2 8#							
Install Notes: Overlay \checkmark Replacement \times							D	orill v	Cut ×			
Step		Description						illustration				
1	Identify the grille & hardware with parts list.											
2	Open the hood and remove the grille shell from the vehicle.											
3	Take out the factory billet grille and hardware from the package. You must be care of doing for protecting the surface of the factory grille from being scratched and damaged. Because the surface is polished and its very bright.											
4	Center the factory grille into the opening of the shell mark and drill point holes in the plastic. Slide the speed clips (it used as a u-nut) onto the flange sides of the shell and threaded the screw into the holes by a phillips screwdriver.											
5	Mark sure the billet grille is centered, tighten the hardware but do not over-tighten.											
6	Installation completed!!!											

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!