




Grille Installation Instruction

Rev. 150116

| | | | |
|-------|------------|-------------|---------------------------------|
| Part# | GR08FGA18A | Application | 03~06 Honda Element (Logo Show) |
|-------|------------|-------------|---------------------------------|

| Parts List | Item | Part Name | QTY | Description | Item | Part Name | QTY | Description |
|------------|------|---------------|-----|-------------|------|-------------------|-----|-------------|
| | 1 | Billet Grille | 1 | Aluminum | 3 | Truss Head Screws | 4 | 6-32x 1.5 " |
| | 2 | Toggle Nuts | 4 | 6# | | | | |

Install Notes: Overlay Replacement Drill Cut

| Step | Description | illustration |
|------|--|--|
| 1 | Identify the grille & hardware with parts list. |  |
| 2 | Take out the factory billet grille and hardware from the package. You must be care of doing this for protect the surface of the factory grille. | N/A |
| 3 | Now place the screws through the holes of the tabs welded rear of the grille, and center the factory grille into the opening. It will only fit one way. Fasten the grille use the toggle nuts from the rear. | N/A |
| 4 | Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten. | N/A |
| 5 | Re-install the grille shell assembly onto the vehicle. | N/A |
| 6 | Installation completed!!! | N/A |

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!