




Grille Installation Instruction

Rev. 190601

Part#	GR08FGA28 A/H	Application	For 2003-2005 Honda Pilot
--------------	--------------------------	--------------------	----------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Truss Head Tapping Screws	4	8#×3"
2	U-Nuts	4	8#	4	Flat Brackets	4		

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Open the hood. Removal of the grille shell is not necessary but is easier to access for installation of the billet insert. At this time, remove the factory grille shell if needed.	
3	Test fit the top billet into the opening factory shell. Install a machine screw .	
4	Into each of the tabs welded to the rear of the billet insert. From the rear of the billet, install bracket, washer and nut (Only hand-tighten the nuts at this time). Re-center the billet in the opening. Tighten the screws until the billet insert is held snugly in place.	
5	Re-install the grille shell onto the vehicle if it was removed.	
6	Installation is now complete.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
We are not responsible for any damage caused by the installation. Thank you for choosing our product!