

Part#	GR08GFH04T	Application	2009 Acura TSX Lower Mesh Grille
-------	------------	-------------	----------------------------------





Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	1	Stainless steel	4	Rectangular Mesh Retainers	2	
	2	Studs	6	6-32 × 1"	5	Universal 3 Hole Mounting Brackets	4	
	3	Kept Nuts	6	6-32				

 Install Notes: Overlay 

 Replacement 

 Drill 

 Cut 

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove the 10 mm hex head bolts retaining the lower air deflector (save for reinstallation). Sit the deflector up against the radiator for access to the lower grille installation hardware or remove it for clearance (save for reinstallation).	
3	Use a flat blade screwdriver to remove the factory front license plate J-clips from the bumper cover.	
4	Thread a screw in a each nut welded to the grille.	
5	Install a rectangular black mesh retainer (bottom outer stud) and black universal 3 hole brackets with nuts (upper outer and mesh retaining studs) onto each of mounting studs (where shown) until the grille is tight against the bumper cover.	
6	Once the lower grille hardware is tightened, reinstall the lower air deflector removed in step 1(not shown)	N/A
7	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!