



PATENT PRODUCT

Grille Installation Instruction

Rev. 190801

Part#	GR08HEE57 C/S/J	Application	For 2008-2010 Honda Accord Main Upper Sedan					
--------------	--------------------	--------------------	--	--	--	--	--	--

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Stainless steel	3	Screws	4	8×1"
	2	Flat Nuts	4	8#				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	N/A
2	Remove the OEM grille shell from vehicle. Cut and remove OEM grille as shown. Then sand smooth.	
3	Hold the billet grille against the OEM grille shell, center and mark holes for drilling. Remove billet grille and drill holes according to your mark.	
4	Secure billet grille using the flat nuts from the back side of the OEM grille shell.	<p style="text-align: center;">Mark and drill 4 holes.</p>
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!