




Grille Installation Instruction

Rev. 190601

Part#	GR08HGA09A/H	Application	For 1994~1997 Honda Accord
-------	--------------	-------------	----------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	5	Kep Nuts	2	10-24
	2	Button Head Screws	2	10-24x1"	6	Two Hole Tab	1	/
	3	Truss Head Tapping Screws	1	8x1/2"	7	'Z' Tabs	1	/
	4	U-Clip Nuts	1	8#				

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Identify the brackets, two shorter is the upper, the longer is the lower. Attach the brackets to the vehicle, using the fastener removed from the vehicle.	
4	Now install the factory grille. Slide the speed clip onto the lower brackets, it used as a U-Nut. Fasten the billet grille using a phillips screwdriver and the screw. Then secure the upper side of the factory grille, place the Allan head bolts through the holes of the brackets and tabs welded the grille and fasten it use the kep nuts from the rear. It may be necessary to slightly bend the brackets to a perfect install.	
5	Make sure the billet grille is centered and tighten the fasteners.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
We are not responsible for any damage caused by the installation. Thank you for choosing our product!