



Grille Installation Instruction

Rev. 20220301

Part#	<i>H87109C&J&S</i>	<i>Application</i>	<i>For 1994-1997 Honda Accord</i>
--------------	----------------------------	--------------------	-----------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Stainless Steel	5	Kep Nuts	2	10-24
	2	Button Head Screws	2	10-24×1"	6	Two Hole Tab	1	/
	3	Truss Head Tapping Screws	1	8×1/2"	7	'Z' Tabs	1	/
	4	U-Clip Nuts	1	8#				

Install Notes: Overlay Replacement Drill Cut

Step	Description
1	Identify the grille & hardware with parts list.
2	Remove factory grille according to OEM manual.
3	Identify the brackets; two shorter ones are for the upper, and the longer ones for the lower. Attach the brackets to the vehicle, using the fastener removed from the vehicle.
4	Now install the Billet grille. Slide the clip nuts onto the lower brackets. Fasten the billet grille with the screws provided. Then secure the upper side of the grille, place the bolts through the holes of the brackets and tabs welded the grille and fasten it use the kep nuts from the rear. It may be necessary to slightly bend the brackets to a perfect install.
5	Make sure the billet grille is centered and tighten the fasteners.
6	Installation completed.

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
 Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
 We are not responsible for any damage caused by the installation. Thank you for choosing our product!