



# PATENT PRODUCT


## Grille Installation Instruction

Rev. 180501

<b>Part#</b>	GR08HGA14S	<i>Application</i>	<b>For 2005-2008 Honda Ridgeline</b>
--------------	------------	--------------------	--------------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Stainless steel	3	Screws	8	8#×2"
	2	U-clip Nuts	8	8#	4	Powder Coated Brackets	4	

**Install Notes:** Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Open the hood of the vehicle, and then remove the plastic filler panel.	
3	Once the filler panel is removed, you can now access the back of the grille. Remove the Phillips screws that hold the factory grille shell into place.	
4	Remove the factory grille shell from the vehicle.	
5	Center the grille into the opening of the factory grille shell. Be sure the screws are through the OEM grille shell.	
6	Place screws through welded aluminum tabs on the grille. Secure grille using the Brackets and U-clip Nuts from the back side of the OEM grille shell.	N/A
7	Make sure the grille is centered and tighten the fasteners.	
8	Reinstall the black plastic cover and the plastic filler panel.	
9	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!