



PATENT PRODUCT


Grille Installation Instruction

Rev. 190601

Part#	GR08HGA15C/S/J	<i>Application</i>	For 2005-2008 Honda Ridgeline 2 Side PCS
--------------	----------------	--------------------	-------------------------------------------------

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
Parts List	1	Billet Grille	2	Stainless steel	3	Screws	4	8# × 1 1/4"
	2	Washers	4	10#	4	Keq Nuts	4	8#

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Center the inserts into the opening of the side bumper pocket.	
4	Mark and drill a 1/8" hole into the plastic of the side bumper pocket, where the tabs that are located on the back each of the billet insert, line up in the pocket.	
5	Secure the screws into each of the tapped tabs on the back side of the billet inserts.	
6	Place the billet grille into the pocket again, being sure that the studs go through the hole that were just drilled out.	
7	Place the powder coated bracket over the stud from the back side of the plastic bumper side pocket. Secure the billet using the keq nuts.	
8	Reinstall the black plastic cover which was removed in step 2.	
9	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.
 Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.
 We are not responsible for any damage caused by the installation. Thank you for choosing our product!