






Part#	GR08HGA19C	Application	For 2005-2007 Honda Odyssey
-------	------------	-------------	-----------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Stainless steel	4	Speed Clips	4	
	2	Allen Head Bolts	2		5	Powder Coated Brackets	2	
	3	K-Lock Nuts	2		6	Screws	4	8#

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Using a flat blade screwdriver all of the plastic clips from the top of the factory grille shell. Figure 1.	 
3	Next remove the plastic clips from the bottom of the grille shell and remove the grille shell from the vehicle. Figure 2.	
4	Center the billet grille into the factory opening and mark and drill the lower mounting holes.	
5	Install the speed clips over the lower lip and in position over the mounting holes drilled in step 4.	
6	Center the billet grille into the opening and attach the lower mounting points using the #8 screws. Figure 3.	 
7	Attach the powder coated brackets to the billet grille using the Allen head bolts and k-lock nuts. Do not fully tighten at this point. Figure 4.	
8	Make sure that the grille is positioned in the opening correctly and mark and drill the upper mounting holes.	
9	Using the #8 screws attach the powder coated brackets to the core support. Figure 4.	
10	Re-center the billet grille to your liking and secure all hardware.	
11	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!