



PATENT PRODUCT Grille Installation Instruction

Rev. 20200801

Part#	H87129C&J&S	Application	For 2006-2008 Honda Pilot
--------------	-------------	--------------------	---------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	#1	Billet Grille	1	Stainless Steel	#4	Z Extension Brackets	2	
	#2	U-Nuts	8	8#	#5	Truss Head Tapping Screws	8	8# x 1"
	#3	L Brackets	2					

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove the radiator cover from the vehicle. Five plastic fasteners hold the grille to the bumper cover along the bottom of the grille. Once these are unfastened the grille can be removed. If you are installing the bumper billet; install at this time.	
3	Center the billet into the opening; note the mounting brackets on the bottom. Slide a U-Nut over the bumper cover holes aligned with the lower mounting tabs. On top, install a U-Nut in each corner.	
4	Attach the Z Extension Bracket with the Truss Head Tapping Screw. Install a U-Nut onto the other end of the brackets. Center the grille, use (4) Truss Head Tapping Screw to attach the lower mounting brackets and corner tabs to the Z Extension Bracket (it may be necessary to slightly bend the brackets with a pair of pliers to achieve the proper alignment).	
5	Re-install the radiator cover. Use the remaining U-Nut and Truss Head Tapping Screws to attach the L Brackets on top of the billet.	
6	Make sure the insert is centered and tighten the hardware.	
7	Reinstall the plastic shroud with the fasteners removed in Step 2.	
8	Installation completed.	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!