






Part#	GR08HGA31A/H	Application	For 2005-2006 Honda CR-V
-------	--------------	-------------	--------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	5	Powder Coated Extension Brackets	2	
	2	Speed Clips	2		6	K-Lock Nuts	2	10-24
	3	Screws	2	8#	7	Hex Bolts	2	3/4" × 1/4"
	4	Allen Head Bolts	2		8	Hex Nuts	2	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Using a flat blade screwdriver remove the 8 plastic clips the hold the upper portion of the grille shell and the front fascia to the filler panel and the vehicle. Figure 1	3 Remove the bolt that goes through the battery hold down and the plastic filler panel. Then remove the plastic filler panel and set it aside as it will be reused later. Figure 2.  
4	Gently rock the grille shell forward and remove the 2 plastic clips that hold the bottom portion of the grille shell to the front fascia. Figure 3.	5 Center the billet grille into the opening and mark and drill the 2 lower mounting holes.  
6	Secure the lower mounts of the billet grille to the vehicle using the supplied clips and screws. Figure 4.	7 Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.
8	Re-center the billet grille and secure all hardware. Reinstall the plastic filler panel, the battery mount and any remaining plastic clips	9 Installation completed!!!

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!