

Grille Installation Instruction

Rev. 180701

Part# GR10FED92V/E Application For 1997-2006 Jeep Wrangler

	Item		Part Name	QTY Descript		tion Item		Part Name		QTY	Description	
Parts Li	st	1	Billet Grille	7	Aluminum		3	Truss Head Screws		21	6-32×1″	
		2	Flange Nuts	21 6#			4	Metal Brackets		21		
Install N	lotes	: Ov	erlay V Re	eplacer	nent ×	D	orill >	(Cut ×			
Step	Description					illustration						
1	Identify the grille & hardware with parts list.					- i						
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation. Position the lower Billet Grille onto grille shell cavity.											0
										14) (F		

Loosely attach the Billet Grille by holding the Metal Brackets behind factory grille shell and inserting the Phillips Screws (from the front) through the Billet Grille holes and Metal Brackets, secure them with Flange Nuts provided.



- 4 Repeat step 3 at top, center, and bottom locations, for all 7 pieces.
- Once the Billet Grilles are loosely attached, center them and tighten all Screws at the same rate.
- 6 Reinstall the black plastic cover which was removed in step 2.
- 7 Installation completed.

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!