

PATENT PRODUCT Grille Installation Instruction

Rev. 20200601

Part#	J65492C&J&S		Applicatio	on F	For 1997-2006 Jeep Wrangler					
	Item	Part Name		QTY	Description	Item	Part Name	QTY	Description	
Parts Li	st #1	Billet G	ille	1	Stainless Steel	#3	Truss Head Screws	21	6-32X1"	
	#2 Flange		Nuts	21	6#	#4	Metal Brackets	21		
Install Notes: Overlay \checkmark Replacement \times Drill \times Cut \times										
Step	Description				illustration					
	ldentify th list.	ne grille	& hardware wi	th part		-#- -=- E	-#			
	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.									
	Thread a Truss Head Screw in each nut welded to the grille. From the rear, place a Metal Bracket on each screw. Now thread a Flange Nut on each screw.									
	(21) 6# Flange Nuts (21) 6-32X1 " Truss Head Screws (21) Metal Brackets									
4	Make sure the insert is centered and tighten the hardware.									
5	Reinstall the plastic shroud with the fasteners removed in Step 2.									
6	Installation completed.									

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!