



Grille Installation Instruction

Rev. 150116

Part#	GR10FED96V	Application	05~07Jeep Liberty (7Pcs)
-------	------------	-------------	--------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	7	Aluminum	3	Truss Head Tapping Screws	14	8×3"
	2	"U" -Clip Nuts	14	8#	4	"U" Powder Coated Brackets	14	

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Identify grille No# as shown. The grille No# can be found on the side or back side of each grille.	
3	Remove the factory grille from your vehicle, be sure there are enough room to work from grille shell back.	N/A
4	Slide the U-Nuts over the brackets provided. Center the billet insert over the opening grille shell, Insert screw into the mounting tabs on the billet grille. Place the bracket on the bar from the rear, screw and fasten the brackets to hold the billet in place.	N/A
5	Complete installation other opening as above. Do not over-tighten the hardware. Re-install the grille onto the vehicle	N/A
6	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.	N/A
7	Reinstall the black plastic cover which was removed in step 2.	N/A
8	Installation completed!!!	N/A

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!