

Part#	GR10FEE51S		Application		For 08~10 Jeep Liberty (7Pcs) – Vertical Billet Grille						
		ltem	Pa	rt Name	QTY	Descriptio	on Ite	m	Part Name	QTY	Description
Parts L	.ist	1	Billet	Grille	7	Stainless ste	el 3	5	Truss Head Tapping Screws	14	8×1 1/2″
		2	Flat N	lut	14	8#	4		Flat Tabs	14	
Install Notes: Overlay \checkmark Replacement \times							Drill × Cut ×				
Step		Description					illustration				
1	Identify the grille & hardware with parts list.										
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.						N/A				
3	Place one screw through each of the welded tabs on the billet grille.										
4	Center the billet grille into the opening of the factory grille shell. Secure the bolt to the threaded holes on the front of the grille.Be sure the bolts are through the OEM grille shell.						N/A				
5	Secure billet grille using the nuts from the back side of the OEM grille shell.						N/A				
6	Make sure the billet grille is centered and tighten the fasteners.but do not over-tighten.						N/A				
7	Reinstall the black plastic cover which was removed in step 2.						N/A				
8	Installation completed!!!						N/A				

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!