

## Grille Installation Instruction

Rev. 190101

Part#	Part#		GR10FFF04V/E		Application		For 2009-2010 Jeep Grand Cherokee				
Parts List		Item	Part Name	e QTY	De	scription	Item	Part Name	QTY	Description	
		1	Billet Grille	7	Alum	inum	3	Screws	14	6-32 X 2"	
		2 Toggle Nuts 14 6		6#							
Install Notes: Overlay   Replacement											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each bolt.										
4	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honeycomb.										
5	Turn the toggle nut so that it is horizontal, and tighten. But not over-tighten!										
6	Repeat steps 3-5 for the remaining billet grille.										
7	Reinstall the black plastic cover which was removed in step 2.										
8	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!