

Installation completed.

6

PATENT PRODUCTGrille Installation Instruction

Rev. 20210401

Part#		J66605A&H Appli		cation	For 2009	For 2009~2010 Jeep Grand Cherokee SRT8							
		Item	Part	Name	QTY	Descrip	tion	Item	Part	Name	QTY	Description	
Parts L	ist	#1 Billet Gri		ille	1	Aluminum		#3	Flat Nuts		4	8#	
		#2 Flat Tabs		s	2				Truss Socket Tapping Screws		4	8×1"	
Install N	es: O	verlay	$\sqrt{}$	Replac	ement >	×	Drill	×	Cut ×				
Step	Description							illustration					
1	Identify the grille & hardware with parts list.												
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.												
3	Thread a Truss Socket Tapping Screw in each nut welded to the grille. From the rear, place (1) Flat Tab on (2) Screws. Now thread a Flat Nut on each screw.												
						(4) Truss (2) Flat To (4) Flat N	abs	Tappin	y Screws				
4	Mal	ke sure	the inse	rt is cente	ered and t	ighten the h	ardware	Э.					

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!