



PATENT PRODUCT




Grille Installation Instruction

Rev. 141230

Part#	GR11FEI62A	Application	2012-2013 Kia SOUL Lower Bumper
--------------	------------	--------------------	---------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Mesh Grille	2	Stainless steel	4	Lock Nut	6	6-32
	2	Flat Tab	6		5	U-Clip Nuts	5	8#-3/4"
	3	stud	6	6-32×1 1/2"	6	Screw	5	8#x1"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell.	
3	Center the billet grille into the opening of the factory grille shell. You need mark and drill four holes. Secure the stud to the threaded holes on the front of the grille. Be sure the stud are through the OEM grille shell.	
4	Secure billet grille using the toggle nuts and j-tab from the back side of the OEM grille shell.	
5	Make sure the billet grille is centered and tighten the fasteners.	
6	Reinstall the black plastic cover which was removed in step 1.	
7	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!