

Grille Installation Instruction

Rev. 141001

Part# GR11GEI57T Application 2014-2015 Kia Sorento Main Upper

		Item	Part Name		QTY	Descrip		ion	Ite	em	Part Name	QTY		Description
Parts L	ist	1	Mesh Grille		1	Stainless stee		:I		3	Lock Nut		7	6-32
		2	2 Flat Tab		7	1			4	4	Stud	,	7	6-32×1 1/2"
Install Notes: Overlay Replacement							×	Dr	ill [√	Cut	×		
Step	Description							illustration						
1	Ide	hardwai	re with pa											
2	You may need to remove the black plastic cover (at the bottom of OEM front bumper) from vehicle. This will allow access to the rear of the grille shell.													
3	Secure the stud to the threaded holes on the rear of the grille.													
4	Center the grille into the opening of the factory grille shell. Be sure the studs are through the OEM grille shell. You need mark and drill three holes.													
5	Secure grille using the flat tabs and lock nuts from the back side of the OEM grille shell.											uts and 7-stud		
6	Make sure the grille is centered and tighten the fasteners.													
7	Reinstall the black plastic cover which was removed in step 2.													
8	Installation completed!!!													

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation.

We are not responsible for any damage caused by the installation. Thank you for choosing our product!