





Grille Installation Instruction

Rev. 181001

Part#	GR11HGJ00A&H	Application	For 2003-2006 Kia Sorento
-------	--------------	-------------	---------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	3	Screws	4	6#-32x2"
	2	Nylon Lock Nuts	4	6#-32	4	Washers	4	6#

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional (for vehicles with black plastic cover under hood), pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Remove the factory grille shell from the vehicle.	
3	Secure the four fully threaded studs into the billet grille.	
4	Place the billet grille into the opening of the vehicle, there are four factory holes that the studs will go into. Once the grille is into place, use one washer and one nylon lock nut per stud and secure the billet grille into place.	
5	Make sure the billet grille is centered and tighten the fasteners.	
6	Reinstall the black plastic cover which was removed in step 2.	
7	Installation completed.	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!