


Part#	GR11HGJ07A/H	Application	For 2005-2008 Kia Sportage
-------	--------------	-------------	-----------------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Aluminum	4	Screws	4	#8
	2	K-Lock Nuts	2		5	Powder Coated L Brackets	2	
	3	Speed Clips	4		6	Fully Threaded Studs	2	2"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. Remove the factory grille shell from the vehicle.	
3	Install the fully threaded studs into the backside of the billet grille.	
4	Secure the powder coated L-brackets to the fully threaded studs using the k-lock nuts.	
5	Place the billet grille into the factory opening and mark and drill the four mounting holes.	
6	Secure the billet grille to the vehicle using the speed clips and #8 screws.	
7	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.	
8	Reinstall the black plastic cover which was removed in step 2.	
9	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!