

Grille Installation Instruction

Rev. 190601

Part# GR12FFE44A/H Application For 2003-2006 Lincoln Navigator

		Item	Part Name	QTY	Descr	iption	Item	Part Name	QTY	Description	
Parts L	ist	1	Billet Grille	1	Aluminum		3	Screws	8	M4×35mm	
		2	Lock Nuts	8	M4		4	Flat tabs	8		
Install N	Note	es: Ov	verlay 🔍	Replac	ement	<u> </u>	ill ×	Cut ×			
Step	Description						illustration				
1	Identify the grille & hardware with parts list.										
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell. Place screws through the welded aluminum tabs on the grille.										
4	Secure the grille using the flat tabs and lock nut from the back side of the OEM grille shell.										
5	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.										
6	Reinstall the black plastic cover which was removed in step 2.										
7	Installation completed!!!										

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!