



# PATENT PRODUCT Grille Installation Instruction

Rev. 20200801

<b>Part#</b>	L85776C&J&S	<b>Application</b>	For 2000-2002 Lincoln LS W/Lower Billet Molding
--------------	-------------	--------------------	---

	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
<b>Parts List</b>	#1	Billet Grille	1	Stainless Steel	#3	Flat Nuts	1	#8
	#2	Phillip Screws	5	#8x5/8"				

**Install Notes:** Overlay  Replacement  Drill  Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.	
3	Center the billet insert below the face bar on the chrome shell. Make sure the billet is centered. Use a #8 screw and flat washer to attach the mounting hole behind the emblem to the billet grille. Center the assembly onto the hood. Mark each mounting hole on the billet grille to the hood. Remove the assembly. Drill a 1/8" hole into the hood at each mark.	
4	For better appearance on lighter color vehicles, apply a coat of matt black spray paint to the area on the hood that can be seen behind the billet grille. Re-install the complete grille shell assembly back onto the vehicle. Use the remaining #8 screws to fasten the billet grille to the hood.	
5	Make sure the insert is centered and tighten the hardware.	
6	Reinstall the plastic shroud with the fasteners removed in Step 2.	
7	Installation completed.	

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!