

Part#	GR12IEG76S/K	Application	For 2000-2002 Lincoln LS
-------	--------------	-------------	--------------------------

Parts List	Item	Part Name	QTY	Description	Item	Part Name	QTY	Description
	1	Billet Grille	1	Stainless steel	3	Nuts	3	6-32
	2	Washers	3	6#	4	Slotted Studs	3	6-32 × 1 1/2"

Install Notes: Overlay Replacement Drill Cut

Step	Description	illustration
1	Identify the grille & hardware with parts list.	
2	Remove the OEM shell (with the chrome piece) from vehicle.	<p>If necessarily, drill 2 holes for 1/4" screw studs</p> <p>Opening for installing grille</p>
3	Install grille to the chrome shell.	<p>Back view</p> <p>Chrome shell</p>
4	Screw studs inside the hole behind of billet grille.	
5	Insert billet grille from front on the opening of factory shell.	
6	Push stud past through honeycomb of factory grille.	
7	Place the washer provided behind over the factory shell bar, let the stud through after nuts.	
8	Repeat step 7 above for each stud until the billet grille lie over the factory shell.	
9	Make sure the billet grille is centered and tighten the fasteners, but do not over-tighten.	
10	Installation completed!!!	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result. Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!