

5

6

7

Installation completed!!!

## Grille Installation Instruction

Rev. 180401

Part#		GR13FFB33A/H			Application	F	For 2007-2009 Mazda CX-7					
		Item	Part Name			QTY	Descriptio			QTY	Description	
Parts L	.ist	2	Billet (		oning Scrows	10	Aluminum 6-32x2"	3	Toggle Nuts	10	6#	
Install N	Note		Truss Head Tapping Screws  verlay  Replacement				Drill    Cut ×					
Step				Descript	ion		illustration					
1	Identify the grille & hardware with parts list.											
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.											
3	Plac	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each screw.										
4	a.Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honeycomb. b.Turn the toggle nut so that it is vertical, and tighten. But not over-tighten! FOR SIDE BILLET GRILLES: Drill a 5/32" hole at each mark. Secure the billets using the screws and nuts provided. Make sure the billets are centered and tighten the fasteners.						M65233				M6 67-33	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Make sure the billet grille is centered and tighten the fasteners.

Reinstall the black plastic cover which was removed in step 2.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!