

## Grille Installation Instruction

Rev. 180401

Part#		GR13FFB33A/H			Application		Fo	For 2007-2009 Mazda CX-7					
		Item		Part N	lame	Q1	ΓΥ	Description	Item	Part Name	QTY	Description	
Parts Li	ist	1 Billet Grille			3	3	Aluminum	3	Toggle Nuts	10	6#		
		2 Truss Head Tapping Screws			1	0	6-32x2"						
Install N	lote	otes: Overlay V Replacement					×	Drill    ✓ Cut ×					
Step	Description							illustration					
1	Identify the grille & hardware with parts list.										<b>★</b> ★ ★ ★ 2		
2	Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.												
3	Place screws through the welded aluminum tabs on the grille, and attach a toggle nut on the end of each screw.												
4	a.Hold the billet insert up to the opening of the factory shell, make sure that it is centered in the grille shell, and push in the toggle nut past the factory grille honeycomb. b.Turn the toggle nut so that it is vertical, and tighten. But not over-tighten! FOR SIDE BILLET GRILLES: Drill a 5/32 hole at each mark. Secure the billets using the screws and nuts provided. Make sure the billets are centered and tighten the fasteners.							M6 6733					
5	Make sure the billet grille is centered and tighten the fasteners.												
6	Reir	nstall th	e black	plastic cov	er which was rei	mov	ed ir	n step 2.					
7	Insta	allation	complet	ted!!!								11.09	

The instruction here is for your reference only. You may need to bend the billet grille bars or tabs a little bit to adjust to fit. We strongly recommend the professional installer for best result.

Please use masking tape and tape the OEM grille shell along the edge to protect your vehicle during installation. We are not responsible for any damage caused by the installation. Thank you for choosing our product!