

Grille Installation Instruction

Rev. 180501

Part#	GR13FFG75A&H		Application		F	For 2010-2013 Mazda CX-9					
	Item	Part Name		QTY	De	Description		Part Name	QTY	Description	
Parts Lis	t 1	Billet Grille		2	Alumir	Muminum		Truss Head Screws	7	6-32×1.5"	
	2	Toggle Nuts		7	6#						
Install Notes: Overlay Replacement											
Step	Description					illustration					
1	Identify the grille & hardware with parts list.										
2	Optional for vehicles with black plastic cover under hood: Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation.										
3	Hold the billet grille against the OEM grille shell, center and mark holes for drilling. Remove billet grille and drill holes according to your mark.										
4	Place screws through the welded aluminum tabs on the grille. Hold the billet grille up to the opening of the factory shell. Thread in the toggle nut from the back of OEM grille honeycomb.										
5	Turn the toggle nut so that it is vertical, and tighten. But not over-tighten.										
6	Reinstall the black plastic cover which was removed in Step 2.										
7	Installation completed.										

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!