

PATENT PRODUCTGrille Installation Instruction

Rev. 20210101

Part#	M66775C&J&S	Application	For 2010-2013 Mazda CX-9
-------	-------------	-------------	--------------------------

Parts List		Item	Part Name	QTY	Description	Item	Part Name	QTY	Description			
		#1	Billet Grille	1	Stainless Steel	#3	Truss Head Screws	7	6-32×1.5"			
		#2	Toggle Nuts	7	6#							
Install Notes: Overlay ✓ Replacement × Drill ✓ Cut ×												
Step	Description					illustration						
1	Identify the grille & hardware with parts list.											
2	Optional: pop hood, remove the black plastic cover (on top of OEM grille) from vehicle. If you are still unable to access the rear, remove the grille shell according to factory manual.											
3	Hold the billet grille against the OEM grille shell, center and mark holes for drilling. Remove billet grille and drill holes according to your mark.											
4	Insert the screws into the weld tab hole from front side of the billet grille.				om front this	picture for reference only; this is not actual grille Weld tab Screw Toggle nut						
5	Center the billet grille onto the OEM grille. Press & insert the toggle nuts on to the rear of the OEM grille through the gap.											
6	Mak	Make sure the insert is centered and tighten the hardware.										
7	Reir	Reinstall the plastic shroud with the fasteners removed in Step 2.										
8	Insta	Installation completed.										

The instruction here is for your reference only. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!