

Grille Installation Instruction

| Part# | GR13GFB81T/H | | Application | | For | For 2004-2008 Mazda RX-8 | | | | | | |
|--|---|-------------|-------------|-----|-------------|--------------------------|--------------|-----------|--|-----|-------------|--|
| Parts List | Item | Part Name | | QTY | Description | | Item | Part Name | | QTY | Description | |
| | t 1 | Mesh Grille | | 1 | Stainless | s steel | 3 | Screws | | 4 | 6-32X1.5" | |
| | 2 | Flat Tabs | | 4 | | | 4 | Kep Nuts | | 4 | 6-32 | |
| Install Notes: Overlay \checkmark Replacement \propto Drill \propto Cut \times | | | | | | | | | | | | |
| Step | Description | | | | | | illustration | | | | | |
| 1 | Identify the grille & hardware with parts list. | | | | | | | | | | | |
| 2 | Optional (for vehicles with black plastic cover under hood), Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation. | | | | | | | | | | | |
| 3 | Test fit the grille to make sure that it fits in the shell properly. Make sure the grille is centered. | | | | | | | | | | | |
| 4 | Thread a screw in each nut welded to the grille. From the rear, place a tab on each screw. Now thread a nut on each screw. | | | | | | | | | | | |
| 5 | Make sure the grille is centered and tighten the fasteners. | | | | | | | | | | | |
| 6 | Reinstall the black plastic cover with the fasteners removed in Step 2. | | | | | | | | | | | |
| 7 | Installation completed!!! | | | | | | | | | | | |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!