

Grille Installation Instruction

Rev. 180301

| Part# | art# | | GR13IFB65A/H | | LADDUCATION | | r 2003-2005 Mazda Mazda 6 Except for s Wagon/s ort Wagon/i Sport Sedan | | | | |
|------------------------------------|---|------|---------------|-----|-------------|-----------|--|-----------------|-----|-------------|--|
| | | Item | Part Name | QTY | Des | scription | Item | Part Name | QTY | Description | |
| Parts L | ict | 1 | Billet Grille | 3 | Aluminu | ım | 4 | Washers | 4 | | |
| | 151 | 2 | Studs | 10 | 6#32 UI | NC×1" | 5 | K-Lock Nuts | 10 | 6#-32UNC | |
| | | 3 | Flat Tabs | 4 | | | 6 | Plastic Washers | 6 | | |
| Install Notes: Overlay Replacement | | | | | | × Dri | il | × Cut × | | | |
| Step | Description | | | | | | illustration | | | | |
| 1 | Identify the grille & hardware with parts list. | | | | | | | | | | |
| 2 | Optional (for vehicles with black plastic cover under hood). Pop hood, remove the black plastic cover (on top of OEM grille / front panel) from vehicle. This will allow access to the rear of the grille shell. If you are still unable to access the rear, remove the grille shell and reattach after installation. | | | | | | | | | | |
| 3 | Center the grille into the opening of the factory grille shell. | | | | | | | | | | |
| 4 | Now thread studs into the grille using a slotted screwdriver. Then push the studs through the grid of the shell.Fasten the grille use the flat tabs, the k-lock nuts and washers from the rear, but do not over-tighten. | | | | | | | | | | |
| 5 | Make sure the grille is centered and tighten the fasteners. | | | | | | | | | | |
| 6 | Reinstall the black plastic cover which was removed in step 2. | | | | | | | | | | |
| 7 | Installation completed!!! | | | | | | | | | | |

The instruction here is for your reference only. You may need to bend the grille a little bit to adjust to fit. We strongly recommend the professional installer for best result. We are not responsible for any damage caused by the installation. Thank you for choosing our product!